



## NORTH AMERICAN SHOOTING SYSTEMS ©

### **.375 and .458 CANADIAN MAGNUM LOADING DATA**

#### **WARNING**

THIS LOADING DATA MUST ONLY BE USED IN RIFLES MANUFACTURED BY NASS.  
AMMUNITION ASSEMBLED WITH THIS DATA MAY BE HAZARDOUS IN OTHER RIFLES.

RELOADING CARTRIDGES SAFELY REQUIRES A GOOD KNOWLEDGE OF ALL FACTORS GOVERNING THIS DISCIPLINE. BEFORE YOU BEGIN, WE SUGGEST YOU OBTAIN AND STUDY A RELOADING MANUAL FROM ONE OF THE MAJOR COMPONENT MANUFACTURERS. IF YOU UNDERSTAND AND FOLLOW THE REQUIRED STEPS CONTAINED IN THESE MANUAL YOU WILL BE CAPABLE OF ASSEMBLING SAFE, RELIABLE AND ACCURATE AMMUNITION.

BECAUSE NASS HAS NO CONTROL OVER THE LOT-TO-LOT VARIATIONS AND DESIGN CHANGES OF THE CARTRIDGE COMPONENTS, **THE STARTING LOAD MUST ALWAYS BE USED 1ST**. WHEN THIS IS FOUND TO BE SAFE, THE MAXIMUM CHARGE MAY BE APPROACHED BY CAUTIOUS 1/2 GRAIN INCREASES IN THE POWDER CHARGE. IF EXCESSIVE PRESSURE SIGNS BECOME EVIDENT, REDUCE YOUR POWDER CHARGE.

#### **.375 and .458 CANADIAN MAGNUM CARTRIDGE SPECIFICATIONS**

Maximum Case Length.....	2.83"	Cartridge Cases.....	CANADIAN MAGNUM
Trim-to Length.....	2.82"	Primer Type.....	Magnum Only
Maximum Loaded Length.....	3.60"	Shell Holder #.....	RCBS #4
Bullet Diameter .375" and .458"		Loading Dies.....	RCBS

**\*\*\*WARNING: NEVER START WITH MAXIMUM LOADS\*\*\***

**\*\*LOADING DATA DEVELOPED IN 26" BARRELS\*\***

\*\*\*\*\*

#### **.375 CANADIAN MAGNUM**

##### **BULLET WEIGHT - 270 GRAINS**

<u>Powder</u>	<u>Starting Loads</u>		<u>Maximum Loads</u>	
	<u>Grains</u>	<u>F.P.S.</u>	<u>Grains</u>	<u>F.P.S.</u>
H 4831	98.0	2848	103	3010

#### **.458 CANADIAN MAGNUM**

##### **BULLET WEIGHT - 500 GRAINS**

<u>Powder</u>	<u>Starting Loads</u>		<u>Maximum Loads</u>	
	<u>Grains</u>	<u>F.P.S.</u>	<u>Grains</u>	<u>F.P.S.</u>
IMR 4064	84.0	2250	89.0	2360

**\*\*\*WARNING: NEVER START WITH MAXIMUM LOADS\*\*\***

IN CANADA: P.O. Box 306, Osoyoos, B.C. V0H 1V0  
IN THE USA: P.O. Box 249, Oroville, WA. 98844  
Telephone (604) 495-3131 Fax (604) 495-2816