Vacuum Heat Treating: Education & Training
Vacuum Technology with The Heat Treat Doctor
Vacuum Brazing with Dan Kay
Vacuum Pump Technology: Education & Training
Metallography with George Vander Voort
Q's and A's
"What's Hot!" Newsletter
Glossary Metallurgical Terms

Deformation and Annealing of Cartridge Brass

May 11, 2015 by George Vander Voort

Abstract

Copper and its alloys are among the most malleable metals and alloys in existence. Cartridge brass, Cu – 30% Zn, has been used for many years to produce cartridge cases for ammunition due to its superior cold forming characteristics. This article shows the microstructure and hardness of cartridge brass from the fully annealed to the heavily cold worked condition. Then, it illustrates the influence of annealing temperature and time on removing the effect of the cold work and returning the alloy to a very low hardness annealed structure.

Introduction

Cartridge brass, Cu – 30% Zn, is a single-phase Cu-based alloy where the addition of zinc increases the strength of copper by solid solution strengthening. The annealed microstructure solidly of zinc is copper at ambient temperature is slightly above 30% Zn. Higher levels of Zn, for example, 40% Zn, produce two-phased (α) brass which is less malleable than the single-phase, α-Cu cartridge brass. Cartridge brass, as the name states, has been used for many years to produce cartridge cases for bullets due to its excellent formability in hot and cold formed conditions. For example, in the example, Figure 1 shows the microstructure of the cartridge case with an annealed cup (a) and two additional cups formed from the annealed cup. Figure 2 shows the microstructure of the forging pin end of a formed 338 caliber cartridge case revealing a heavily cold worked microstructure. Color etching is far more effective than black & white etching to reveal the complete grain structure and deformation. Comparisons of color vs. B&W etching will be presented later.

Experiment

Specimens of hot extruded and fully annealed cartridge brass were cold rolled 15, 30, 40, 50, 60 and 70% in thickness. Specimens were mounted and polished and etched using the commonly used B&W etchant of equal parts of ammonium hydroxide and hydrogen peroxide (3% conc.) mixed before use. Figure 3 and 3a, 3 and 3, 4 and 4, and 5 and 5 show B&W images of longitudinal planes from the annealed (Fig. 3 and the cold worked cartridge brass specimens (30, 40, 50, 60 and 70% cold reductions). Figures 3 and 3, 4 and 4, and 5 and 5 show color images using Klemm's III tint etch and polarized light for the cold worked specimens (15, 30, 40, 50, 60 and 70% cold reductions). These images reveal that the grain are becoming elongated with cold reduction, with increasing lengthwidth ratio with increasing cold reduction, plus greater amounts of slip deformation. Hardness measurements on these specimens ranged from 57.9 ± 0.8 HR in the starting fully annealed condition to 231.9 ± 7.9 HV after a 70% cold reduction in thickness, a fourfold increase in hardness.

Annealing experiments were conducted on a number of the cold worked specimens. Figures 5a and 6 show color etched images of the specimens cold rolled 50% and then annealed 30 minutes at 500 and 700°F. No difference in the microstructure is seen in the specimen annealed at 500°F when Figures 5a and 6 show annealed at 700°F. Figures 3 and 3, 4 and 4, and 5 and 5 show B&W images of longitudinal planes from the annealed (Fig. 3 and the cold worked cartridge brass specimens (30, 40, 50, 60 and 70% cold reductions). Figures 5 and 8, 3 and 3, and 5 and 6 show color images using Klemm's III tint etch and polarized light for the cold worked specimens (15, 30, 40, 50, 60 and 70% cold reductions). These images reveal that the grain are becoming elongated with cold reduction, with increasing lengthwidth ratio with increasing cold reduction, plus greater amounts of slip deformation. Figure 5 shows the microstructure of the specimen cold rolled 50% and then annealed 30 minutes at 500°F which is not recrystallized. Figure 6 shows the same specimen but cold rolled 50% and then annealed 30 minutes at 700°F. Figures 5a and 6 show color images using Klemm's III tint etch and polarized light for the cold worked specimens (15, 30, 40, 50, 60 and 70% cold reductions). Figures 7a and 6 show that the specimen cold rolled 50% and then annealed 30 minutes at 700°F is recrystallized. Figures 7a and 6 show color images using Klemm's III tint etch and polarized light for the cold worked specimens (15, 30, 40, 50, 60 and 70% cold reductions). Figures 7a and 6 show that the specimen cold rolled 50% and then annealed 30 minutes at 700°F is recrystallized.

Hardness tests, 100 g or a 100 gf load, were made on the original hot extruded and fully mill-annealed starting material and on the hot extruded, annealed and 50% cold reduced specimen and for similar 50% CR specimens that were annealed for 30 minutes at 500, 700, 800 and 1300°F. Note that the distribution curves for the 50% CR specimen and the 50% CR specimen annealed at 500°F for 30 minutes are essentially identical, which is not surprising based on the image in Figure 5a which shows no influence of annealing at 500°F on the microstructure. As the annealing temperature is increased from 700 to 1300°F, the HV distribution curves become more peaked as the hardness decreases. The distribution curve for the starting fully annealed specimens is the lowest in hardness as 35 minutes at 700°F yielded slightly greater hardness. Figure 10 plots the mean Vickers hardness for each of the 50% CR specimens from the initial non-annealed condition (just after cold rolling) and temperature versus the 30 minute hold at each annealing temperature from 500 to 1300°F.

Conclusions

The experiment illustrates the extreme malleability of cartridge brass, Cu – 30% Zn, which has been used for many years to build cartridge cases for bullets. Cold working increases the hardness of the alloy dramatically: a 400% increase was obtained going from the fully annealed condition to a 70% reduction in thickness. The grains become thinner and more elongated with increased cold reduction – anisotropic in grain shape. Along with the increased strength, the cold working treatments increase ductility enough to provide good service performance. The re-annealing experiments showed how recrystallization begins slowly, and with duplex appearing grains are distributions until the recrystallization temperature becomes quite high resulting in a coarse grained twinned structure with a uniform grain size distribution. The results also demonstrate the value of color tint etching and polarized illumination for revealing preferred versus random crystallographic textures.

Starting Annealed Microstructure of Cu-30% Zn Cup

Figure 1: Solid annealed microstructure of a cartridge brass cup to be cold drawn into a cartridge for larger size bullets. The CA number at left and the ID number is at the right; transverse orientation (Klemm's III color etch, polarized light, 50X).

Cold Work at Firing Pin of a 338 Caliber Cartridge Case

Figure 2: Heavily cold worked structure at the firing pin region of a 338 caliber cartridge case (Klemm's III, polarized light, 50X).

Cu–30% Zn, Hot Extruded, Annealed and Cold Rolled

Left: Annealed Starting Condition; 57.9 ± 4.8 HV

Right: Cold Rolled 15%; 139.8 ± 10.4 HV

Figure 3a and b: Microstructure of cartridge brass (Cu – 30% Zn) with 0% (left) and 15% (right) cold reduction in thickness. Note the equiaxed grains with annealing twins in the starting condition and the slip lines with deformed grains after 30% reduction. Etched with equal parts ammonium hydroxide and hydrogen peroxide (3% conc.). Originals at 100X magnification. Magnification bars are 100 μm long.

Left: Cold Rolled 40%; 185.3 ± 6.2 HV

Right: Cold Rolled 50%; 194.3 ± 2.1 HV

Figures 3a and 3: Microstructure of cartridge brass (Cu – 30% Zn) with 40% (left) and 50% (right) cold reduction (in thickness). Note the heavy slip lines with highly elongated grains after 40 and 50% reduction. Etched with equal parts ammonium hydroxide and hydrogen peroxide (3% conc.). Originals at 100X magnification. Magnification bars are 100 μm long.

Left: Cold Rolled 40%; 185.3 ± 6.2 HV

Right: Cold Rolled 50%; 194.3 ± 2.1 HV

Figures 3b and 3: Microstructure of cartridge brass after cold reduction. Klemm's III, 3 mm., polarized light and sensitive tint.

Left: Cold Rolled 60%; 198.6 ± 5.2 HV

Right: Cold Rolled 70%; 231.9 ± 7.9 HV

Figures 3 and 3: Microstructure of cartridge brass (Cu – 30% Zn) with 60% (left) and 70% (right) cold reduction (in thickness). Note the heavy slip lines with highly elongated grains after 60 and 70% reduction. Etched with equal parts ammonium hydroxide and hydrogen peroxide (3% conc.). Originals at 100X magnification. Magnification bars are 100 μm long.

Left: Cold Rolled 60%; 198.6 ± 5.2 HV

Right: Cold Rolled 70%; 231.9 ± 7.9 HV

Figures 3b and 3: Microstructure of cartridge brass after cold reduction. Klemm's III, 3 mm., polarized light and sensitive tint.

Influence of Cold Reduction on Hardness of Cu – 30% Zn



Figure 4: Cold reduction (in 70% of the original thickness caused a fourfold increase in Vickers hardness.

HV of Cold Worked and Annealed Cu-30% Zn



Figure 9: The fully annealed specimen was cold reduced 50% in thickness. Then, DR specimens were annealed for 30 minutes at 500, 700, 800 and 1300°F. Microhardness tests were prepared metallographically and 100 HV indents at 100 gf load were made in each. The plot shows the distribution of HV values for each specimen.

Figure 10: This is a plot of the mean Vickers hardness values starting with the specimen cold reduced 50% at room temperature and then showing the effect of 30 minute time at temperatures from 500 to 1300°F.

Cu–30% Zn, Hot Ext., Cold Red. 50%, Annealed

Left: 500°F/30M °C – 30 minutes

Right: 700°F/30T °C – 30 minutes

Figure 5a and b: Microstructure of wrought cartridge brass, Cu-30% Zn, cold reduced 50%, and annealed, 500°C (500°F) for 30 min. (a) widely after the cold worked FCC grains (more slip lines) and annealing twins; 315°C (700°F) for 30 min. produced partial recrystallization. Tint etched with Klemm's I reagent (Originals at 100X, crossed polarized plus sensitive tint).

Cu–30% Zn, HE, CR 50%, Annealed 800 °F/427 °C

Left: 4 minutes

Right: 8 minutes

Figures 6 and 6: Microstructure of wrought cartridge brass, Cu – 30% Zn, cold reduced 50%, and annealed at 427°C (800°F). 4 minutes did not visibly affect the cold worked grain structure (note steep slip lines). 8 minutes has fully recrystallized the FCC grains (Klemm's I reagent (Originals at 100X, crossed polarized light tint etch revealed grain structure).

Left: 15 minutes

Right: 30 minutes

Figures 6a and 6: Microstructure of wrought cartridge brass, Cu – 30% Zn, cold reduced 50%, and annealed at 427°C (800°F). 15 minutes has partially recrystallized the FCC grain structure with some remaining coarse cold worked grains. 30 minutes has increased the degree of recrystallization. Tint etched with Klemm's I (originals at 100X, crossed polarized light (off crossed).

Cu–30% Zn, HE, CR 50%, Annealed 700°F/1652 °C

Left: 15 minutes, Off Rt Original 100X

Right: 60 minutes, XP+ST, 100X

Figures 7a and 6: Microstructure of wrought cartridge brass, Cu – 30% Zn, cold reduced 50% annealed at 482°C (900°F) – 15 min. has fully recrystallized the FCC grain structure, but it has a duplex grain size distribution; 60 min. has increased the grain size. Tint etched with Klemm's III.

Cu–30% Zn, HE, CR 50%, Annealed 1300°F/704 °C – 30 min.

Left: MnLOH – H2O2

Right: Klemm's I, XP+ST, Original at 50X

Figure 8a and b: Microstructure of wrought cartridge brass, Cu – 30% Zn, cold reduced 50% and annealed at 704°C (1300°F) – 30 min. producing a fully recrystallized, and grown, equiaxed FCC grain structure with annealing twins. Polarized light and sensitive tint.

Left: Klemm's III, Original at 50X

Right: Beraha's PbCl, Original at 50X

Figures 8a and 8: Microstructure of wrought cartridge brass, Cu – 30% Zn, cold reduced 50% and annealed at 704°C (1300°F) – 30 min. producing a fully recrystallized, and grown, equiaxed FCC grain structure with annealing twins.

George Vander Voort has a background in physical, process and mechanical metallurgy and has been performing metallographic studies for 47 years. He is a long-time member of ASTM Committee E-4 on metallography and has published several environmentally-sensitive failure analysis. He regularly teaches MSE courses for ASM International and is now doing webinars. He is a consultant for Struers Inc. and will be teaching courses (and for them) can be reached at 440-523-7648, (SMA), georgevandervoort@yahoo.com and through his web site: **www.georgevandervoort.com**

To View a listing of all George's Articles please click here

Read George Vander Voort's Biography

Specialists in Vacuum Furnace Technology - High Quality Vacuum Furnace Manufacturer

COMPANY
WHY VAC AERO? Products & Services
Company History
Certificates & Approvals
Employment Opportunities
Values & Commitment
Corporate Sponsorship
Corporate Brochure
Terms & Conditions of Use
Privacy Policy

FURNACE MANUFACTURING
Horizontal Furnace Specs
Vertical Furnace Specs
Hot Zones
Control Systems
Custom Vacuum Furnaces
Quality Control
Service & Support
Furnace Request for Quote
RFQ's Items

THERMAL PROCESSING
Ontario – Plant 1
Ontario – Plant 2
Quebec – Thermal Processing Division
Specific Heat Treating & Brazing Approvals
Metallurgical Services Matrix

COATINGS
Quebec Coatings Division
HVOF Spray System
Specific Coating Approvals
Metallurgical Services Matrix

SERVICES & SUPPORT
Furnace Rebuilds & Upgrades
Hot Zone Rebuilds
Process Controls Upgrades
Ordering Parts
Field Service
Training Seminars

Providing Engineering Excellence & Support in Furnace Manufacturing & Metallurgical Services Since 1999

Site Map Contact Terms and Conditions Privacy

© Copyright 2016 VAC AERO - All rights reserved.