



270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:10"

| Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|----------------------|--------------------|-------------------|-------------------|----------------------|------------------------|
|----------------------|--------------------|-------------------|-------------------|----------------------|------------------------|

| | | | | | |
|------|--------|-------|-------|-------|--------|
| 85gr | TSX FB | 30254 | 0.158 | 0.246 | 3.080" |
|------|--------|-------|-------|-------|--------|

| | | | | | |
|------|--------|-------|-------|-------|--------|
| 85gr | MPG FB | 30249 | 0.158 | 0.229 | 3.100" |
|------|--------|-------|-------|-------|--------|

| Powder | Minimum | | Maximum | |
|-----------------|------------------------|-----------------------|------------------------|-----------------------|
| | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) |
| IMR 4320 | 50.0 | 3333 | 55.5 | 3673 |
| RL 15 | 50.4 | 3393 | 56.0 | 3718 |
| Win 760 | 55.5 | 3408 | 61.7c | 3721 |
| A-2700 | 56.3 | 3459 | 62.5c | 3755 |
| Varget | 52.2 | 3457 | 58.0c | 3796 |
| H380 | 57.4 | 3571 | 63.7c | 3799 |
| Big Game | 56.7 | 3513 | 63.0c | 3801 |
| PowerPro 2000MR | 55.0 | 3500 | 61.1 | 3834 |



270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:10"

| Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|
| 95gr | TTSX BT | 30271 | 0.177 | 0.292 | 3.100" |
| Minimum | | | Maximum | | |
| Powder | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | |
| RL 15 | 49.3 | 3259 | 54.8 | 3603 | |
| Win 760 | 54.1 | 3330 | 60.1c | 3604 | |
| H4350 | 55.9 | 3266 | 62.1c | 3611 | |
| A-2700 | 55.3 | 3360 | 61.5c | 3650 | |
| Big Game | 54.9 | 3361 | 61.0c | 3656 | |
| H380 | 55.2 | 3413 | 61.3c | 3670 | |
| RL 17 | 54.1 | 3274 | 60.1c | 3673 | |



270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:10"

| Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|----------------------|------------------------|-----------------------|------------------------|-----------------------|------------------------|
| 110gr | TSX BT | 30260 | 0.205 | 0.323 | 3.240" |
| 110gr | TTSX BT | 30274 | 0.205 | 0.377 | 3.250" |
| | | Minimum | Maximum | | |
| Powder | Charge (grains) | Velocity (fps) | Charge (grains) | Velocity (fps) | |
| RL 15 | 47.2 | 3075 | 52.5 | 3342 | |
| Win 760 | 51.7 | 3089 | 57.5 | 3373 | |
| H4350 | 53.0 | 3068 | 58.9c | 3381 | |
| A-2700 | 52.0 | 3101 | 57.8c | 3404 | |
| H380 | 51.7 | 3138 | 57.5c | 3407 | |
| Hybrid 100V | 53.2 | 3175 | 59.1c | 3448 | |
| RL 17 | 52.2 | 3132 | 58.0c | 3474 | |
| Hunter | 59.1 | 3260 | 65.7c | 3507 | |



270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:10"

| Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|----------------------|--------------------|-----------------------|-------------------|-----------------------|------------------------|
| 129gr | LRX BT | 30262 | 0.240 | 0.463 | 3.300" |
| 130gr | TSX BT | 30264 | 0.242 | 0.374 | 3.250" |
| 130gr | TTSX BT | 30276 | 0.242 | 0.392 | 3.210" |
| | | Minimum Charge | Velocity | Maximum Charge | Velocity |
| | | (grains) | (fps) | (grains) | (fps) |
| Powder | | | | | |
| Win 760 | | 48.1 | 2812 | 53.5 | 3093 |
| H4350 | | 49.7 | 2845 | 55.3 | 3116 |
| H4831sc | | 54.5 | 2847 | 60.5c | 3116 |
| StaBall 6.5 | | 50.5 | 2865 | 55.7 | 3140 |
| Hybrid 100V | | 49.0 | 2818 | 54.4 | 3151 |
| IMR 4350 | | 50.2 | 2857 | 55.7c | 3165 |
| IMR 4831 | | 51.3 | 2861 | 57.0c | 3167 |
| A-4350 | | 51.5 | 2842 | 57.2c | 3168 |
| PowerPro 4000MR | | 51.0 | 2870 | 55.5 | 3185 |
| RL 17 | | 48.7 | 2877 | 54.1 | 3187 |
| Superformance | | 52.5 | 2850 | 58.3c | 3193 |
| RL 19 | | 53.6 | 2890 | 59.5c | 3207 |
| Hunter | | 53.8 | 2956 | 59.8c | 3211 |



Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Twist Rate: 1:10"

Primer: Rem 9 1/2

| | Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|-----|---------------|-------------|------------|------------|---------------|-----------------|
| | 140gr | TSX BT | 30266 | 0.261 | 0.404 | 3.210" |
| | | Minimum | | Maximum | | |
| | | Charge | Velocity | Charge | Velocity | |
| | Powder | (grains) | (fps) | (grains) | (fps) | |
| | H4350 | 48.9 | 2704 | 54.4 | 2995 | |
| | IMR 4831 | 50.1 | 2712 | 55.6c | 3009 | |
| | H4831sc | 54.3 | 2736 | 60.3c | 3018 | |
| | IMR 4350 | 49.4 | 2703 | 54.9 | 3025 | |
| Win | Supreme 780 | 52.4 | 2715 | 58.2c | 3026 | |
| | Hybrid 100V | 48.0 | 2686 | 53.3 | 3027 | |
| | A-4350 | 49.9 | 2719 | 55.5c | 3032 | |
| | RL 17 | 48.1 | 2731 | 53.5 | 3065 | |
| | Hunter | 52.5 | 2823 | 58.4c | 3076 | |
| | RL 19 | 52.3 | 2757 | 58.1c | 3080 | |
| | Superformance | 51.5 | 2762 | 57.2c | 3082 | |



270 Winchester Load Data

Case: Remington

Barrel Length: 24"

Case Trim Length: 2.530"

Primer: Rem 9 1/2

Twist Rate: 1:8"

| Bullet Weight | Bullet Type | Bullet SKU | Bullet S.D | Bullet G1 B.C | Cartridge O.A.L |
|---------------|-------------|-------------------------|------------------------|-------------------------|------------------------|
| 150gr | TSX FB | 30269 | 0.279 | 0.386 | 3.210" |
| 155gr | LRX BT | 32112 | 0.289 | 0.540 | 3.340" |
| | | Minimum Charge (grains) | Minimum Velocity (fps) | Maximum Charge (grains) | Maximum Velocity (fps) |
| IMR 4955 | | 46.5 | 2454 | 51.7 | 2762 |
| IMR 4831 | | 46.2 | 2505 | 51.3 | 2786 |
| H4350 | | 43.6 | 2540 | 48.4 | 2796 |
| Win 760 | | 44.2 | 2553 | 49.1 | 2805 |
| A-4350 | | 47.5 | 2569 | 52.8c | 2841 |
| IMR 4350 | | 46.8 | 2569 | 52.0 | 2843 |
| H4831sc | | 51.7 | 2591 | 57.4c | 2850 |
| RL 17 | | 44.2 | 2579 | 49.1 | 2862 |
| Hybrid 100V | | 47.1 | 2580 | 52.3 | 2864 |
| StaBall 6.5 | | 47.0 | 2558 | 52.3 | 2874 |
| Hunter | | 49.1 | 2635 | 54.6c | 2884 |
| RL 23 | | 48.4 | 2621 | 53.7 | 2888 |
| Superformance | | 48.8 | 2603 | 54.2 | 2899 |
| Win | Supreme 780 | 51.8 | 2600 | 57.5c | 2900 |
| | RL 19 | 50.3 | 2618 | 55.9c | 2935 |

Notes

150gr TSX FB requires 1:9.5" twist or faster.

155gr LRX BT requires 1:8" twist or faster.